



HOT OIL FLUSHING UNIT



Equipment No: HOF-004

Specifications

- Hot Oil Flushing
- Flowrate : 600 Lpm
- Max. Pressure : 15 bar
- Work Pressure : 10 bar
- Power (E) : 415-440V/3ph/50Hz
- Star-Delta Start
- Running Amps : 82 Amps

Weights & Dimensions

Overall Length	:	2240 mm
Overall Width	:	1555 mm
Overall Height	:	1940 mm
Overall Weight	:	Approx. 2000 kg

Key Features

Built-in Tank	:	1130 Litres (L1450 x W1000 x H780 mm)
Pump	:	Veljian Vane Pump, VT6ED-085-B45-1R03-B1 c/w Relief valve VR5V12-393-12-A1 , Check Valves VC5V10+321-B1 & VC5V12-321-A1
E-Motor	:	WES WLS225M-4 B3, 45kW
E-Heater	:	20 kW, Max.Temp : 100°C
Filtration	:	Pall UR310F4020ZG Rated 41 bar (600 psi)
Diaphragm Pump	:	ARO PD10P-APS-PTT

Connections

Inlet	:	3 x 2" Female NPT
Outlet	:	3 x 2" Female NPT

Other Info

Built	:	August 2019
Location	:	Malaysia

Oilfields Energy Solutions Sdn Bhd

B1-5-3 Solaris Dutamas
Jalan Dutamas 1, 50480
Kuala Lumpur

Email : info@oesgrp.com